

RESILIENT TILE FLOORING - QUIETLOK® CONTINENTAL

COLLECTION/PATTERN: ZINC

PRODUCT ID: QLC-ZNC-20H-5.0


QUIETLOK®

TECHNICAL SPECIFICATIONS

SIZE	9.56" x 60" (242mm x 1524mm)
WEAR LAYER THICKNESS	20MIL (0.5mm)
OVERALL THICKNESS	5.0mm (0.20")
CORE THICKNESS	4.0mm (0.16")
CORE MATERIAL	SPC RIGID CORE
PAD	1mm (0.04") IXPE FOAM PAD
EDGE DETAIL	MICRO-BEVEL
EMBOSSING	DEEP OVERALL EMBOSSING
FINISHING	3-LAYER CERAMIC BEAD UV COATING
COVERAGE/CARTON	8 PIECES (31.89 sq.ft)
COVERAGE/PALLET	48 CARTONS (1,530.72sq.ft)
COVERAGE/CONTAINER	16 PALLETS (24,491.52 sq.ft)
LIMITED WARRANTY	15 YEAR COMMERCIAL
RATINGS	STC 51 & IIC 54



PRODUCT COMPONENTS



- 1 DURABLE WEAR LAYER**
 - 3-LAYER SCRATCH RESISTANT UV COATING
 - 20-MIL CLEAR WEAR LAYER
- 2 VINYL DECOR LAYER**
- 3 2G CLICK SYSTEM**
 - LOCKS ON BOTH LONG & SHORT SIDES
- 4 SPC RIGID CORE**
 - INCREASED DENSITY
 - MORE DIMENSIONAL STABILITY
- 5 IXPE FOAM PAD**
 - HIDES SUBFLOOR IMPERFECTIONS
 - REDUCES DEFLECTION
 - DECREASES SOUND TRANSMISSION

MGROUP

OFFICE: 706.350.4300 | INFO@QUIETLOK.COM
WWW.MGROUPCORP.COM/QUIETLOK/

REV. DATE - 04/2025

